



Butterfly Hanger for 1/2 in or 3/8 in coaxial cable and elliptical waveguide 180, 220, and 240

## Product Classification

**Product Type** Hanger kit

## Dimensions

**Nominal Size** 1/2 in  
**Compatible Diameter, maximum** 16.256 mm | 0.640 in  
**Compatible Diameter, minimum** 10.414 mm | 0.410 in  
**Height** 31.75 mm | 1.25 in  
**Length** 40.64 mm | 1.60 in  
**Width** 38.10 mm | 1.50 in

## Electrical Specifications

**DTF Effect** 0.1 dB  
**Return Loss Effect** 0.1 dB

## Environmental Specifications

**Operating Temperature** -40 °C to +85 °C (-40 °F to +185 °F)

## General Specifications

**Hanger Type** Standard butterfly hanger  
**Cables per Hanger** 1  
**Color** Silver  
**Material Type** Stainless steel  
**Ordering Note** CommScope® standard product in Mexico, Central America, and South America | CommScope® standard product in the United States and Canada  
**Package Quantity** 10

## Mechanical Specifications

**Corrosion Resistance, minimum with no degradation** =500 hours in salt spray chamber  
**Mounting** 3/8 in (M10) drilled cable ladder  
**Vibration Survival** =4 hours at resonant frequency  
**Environmental Strength Capability** Double cable weight

## Packed Dimensions

<b>Height</b>	14.8 cm   5.8 in
<b>Length</b>	9.0 cm   3.5 in
<b>Shipping Weight</b>	0.34 kg   0.75 lb
<b>Width</b>	10.6 cm   4.2 in

## Regulatory Compliance/Certifications

### Agency

RoHS 2011/65/EU

ISO 9001:2015

China RoHS SJ/T 11364-2014

### Classification

Compliant

Designed, manufactured and/or distributed under this quality management system

Above Maximum Concentration Value (MCV)

