

## SureGround® Grounding Kit for 1/2 in coaxial cable



### Product Classification

<b>Brand</b>	SureGround®
<b>Product Type</b>	Grounding kit

### Dimensions

<b>Nominal Size</b>	1/2 in
<b>Bonding Conductor Length</b>	609.6 mm   24 in
<b>Cable Jacketing Removal Length, maximum</b>	38.1 mm   1 1/2 in
<b>Cable Jacketing Removal Length, minimum</b>	38.1 mm   1 1/2 in
<b>Compatible Diameter, maximum</b>	16.510 mm   0.650 in
<b>Compatible Diameter, minimum</b>	15.494 mm   0.610 in

### Electrical Specifications

<b>Current Handling</b>	Tested to withstand 100,000 amps peak current surge
<b>Current Handling Test Method</b>	MIL-STD-1757
<b>Grounding, Bonding and Shielding Test Method</b>	MIL-STD-188-124A
<b>Lightning Protection Test Method</b>	IEC 1024-1

### Environmental Specifications

<b>Operating Temperature</b>	-40 °C to +85 °C (-40 °F to +185 °F)
<b>Storage Temperature</b>	-40 °C to +80 °C (-40 °F to +176 °F)
<b>Weatherproofing Method</b>	Butyl and electric tape

### General Specifications

<b>Grounding Kit Type</b>	SureGround® Grounding Kits
<b>Cable Type</b>	Corrugated   Smoothwall
<b>Ordering Note</b>	CommScope® standard product (Global)
<b>Color</b>	Black
<b>Bonding Conductor Material</b>	Copper
<b>Bonding Conductor Wire Size</b>	6 gauge
<b>Bonding Conductor Jacketing Material</b>	PVC
<b>Grounding Strap Material</b>	Tinned copper

# SG12-06B2A

---

<b>Includes</b>	Grounding kit   Hardware   Lug   One roll of 2 in PVC tape   One roll of 24 in butyl rubber tape
<b>Locking Bail Material</b>	Stainless steel
<b>Lug Attachment</b>	Factory attached
<b>Lug Type</b>	Two-hole lug
<b>Package Quantity</b>	1
<b>Rivet Material</b>	Tinned copper

## Mechanical Specifications

<b>Blowing Rain Test Method</b>	MIL-STD-810, Method 506
<b>Corrosion Test Method</b>	MIL-STD-1344, Method 1001
<b>Freezing Rain/Icing Test Method</b>	MIL-STD-810, Method 521
<b>Humidity Test Method</b>	MIL-STD-1344, Method 1002
<b>Immersion Test Method</b>	IEC 60529:2001, IP68
<b>Thread Size</b>	3/8 in
<b>UV Resistance Test Method</b>	MIL-STD-810, Method 505
<b>Vibration Test Method</b>	MIL-STD-202, Method 214

## Packed Dimensions

<b>Height</b>	447.0 mm   17.6 in
<b>Length</b>	177.8 mm   7.0 in
<b>Shipping Weight</b>	0.59 kg   1.30 lb
<b>Width</b>	395.2 mm   15.6 in

## Regulatory Compliance/Certifications

<b>Agency</b>	<b>Classification</b>
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system



## Included Products

- 9905-71 — Black 2 in PVC Tape, 20 ft
- 42615-10 — Butyl Rubber Tape, 24 in

## \* Footnotes

<b>Grounding, Bonding and Shielding Test Method</b>	Military Standard for Grounding, Bonding, and Shielding: Bond Resistance Requirement of a Maximum dc resistance of 0.001 ohm
---	--

## Lightning Protection Test Method

Protection Against Lightning Electromagnetic Impulse, Table 1—Protection Level III–IV, 1995-02